


## KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL

Taps | Electronic taps



### KWC-No.

**3600001583**

stainless steel, A 125, flexible connection hoses, without drain fitting, battery, with mixing

- \* Automatic, non-contact, basin
- opto-electronic controlled
- \* Made of stainless steel
- \* With mixing
- adjustable, twist-proof temperature stop
- \* EcoProtect - water-saving device
- \* Control electronics
- 24-hour hygiene flushing adjustable
- Safety shutdown in case of continuous reflection
- Storage of statistical data
- \* Fixed spout
- Neoperl® Perlator® SSR, swivelling jet regulator

- \* Electrovalve
- \* Flexible connection hoses 3/8"
- \* QuickInstallation - Fastening via threaded connection M33 x 1.5 with locking screws
- \* Mounting hole size 35 mm
- \* Scope of delivery:
  - Battery compartment including battery 6V Lithium CRP2 for mounting under the washbasin
- \* Order separately (optional or if required):
  - Possibility of parameterization via bidirectional remote control, or C-module (3600001331) with an app



### Technical Data

Electronical control
Connection
Spout
Power supply
Color code
Installation_type
Faucet_typ
Measure Height
Projection_A

NW 3/4"1
Flexible connection hoses 1
NW 1/2"1
NW 1/2"1
stainless steel
NW 1/2"1
G 3/4"1
165
A 125



### Optional Accessories





## KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL

Taps | Electronic taps

**Bidirectional remote control for  
electronical fittings F3 and F5**

**2030036654**  
ACEX9005

**2-button remote control for fittings F3  
and F5**

**2030036849**  
ACEX9004

**C module**

**3600001331**  
ACEX9020