
## KWC ONO touch light PRO









KWC-No.

Finish

all chrome

12.651.031.000FL

A 125, flexible connection hoses, with pop-up valve, mains receiver

## Basin with LED-technology

IntelligentControl - electronic control

- touch light PRO technology
- touch'n'flow 1-2-3
- 3 preset temperatures and flow rates
- Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- duration of water flow safety indication: switch off automatically after 10 minutes
- temperature limit can be adjusted
- hot water disinfection (5 minutes) can be adjusted
- can be restored to factory settings
- Swivel spout 360°
- Neoperl® SLIM®
- touch light PRO control unit, maintenance-free
- up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- incl. installation materials
- designed for wired connection to 1 operating unit (standard)
  , wireless connection to 1 operating unit (optional)
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
- Mains receiver 100-240 V / operating voltage 15 V / cable length 900 mm
- Control unit and wired operating unit / cable length 2000 mm
- KWC pop-up valve Z.538.581.000
- To be ordered separately:
- Rough in for operating unit Z.636.183
- To be ordered separately (optional or if necessary):
- Extension set 1500 mm Z.536.352, comprising: stainless steel

hose 1500 mm, ¾" x ¾", double nipple, sealing material – KWC ONO touch light PRO wireless operating unit Z.536.351.000

• Go to www.kwc.com for comprehensive information on planning, installation and operation, or get in touch with your KWC contact person.