





HEALTHCARE TAPWARE

TOUCH MASTERMIX thermostatic shower tablet - Downward outlet - 75710



Benefits of the product

MASTERMIX RANGE

- Ingenious combination of two solenoid valves and thermostatic cartridge: safety and reliability.
- No cross-connection between hot water and cold water.
- Without check-valves
- A simple light touch on the button will activate or stop the water flow.
- Suitable for mobility-impaired and children. Autoflush adjustable by the technical staff. Limits the bacterial proliferation (legionella, pseudomonas...)
- Cold body: anti-scalding insulation
- Body with smooth interior: limits the risk of bacterial proliferation
- Dual safety temperature limiter (38°C and 41°C)
- Temperature stability and anti-scalding safety
- Quick and easy Installation and maintenance.
- Safe thermal shock: only accessible by technical staff
- Shower tablet: easy cleaning, no corners, nooks
- "Shelf/tablet" function
- Excentric connectors with 1/4 turn stop valves included
- Body docking with the wall: optimized cleaning of all contact surfaces

Description

Shower thermostatic tablet without mixing chamber under pressure (avoiding DHW and DCW intercommunication upstream of the shutter), with MASTERMIX conception, equipped with ergonomic swivel knob, in chrome-plated zamak, and with TOUCH soft activation button. Temperature knob with dual temperature limiter 38°C and 41°C. Safety temperature unlocking for thermal shock, and accessible only by technical staff, without dismantling the knob. Connection exclusively by means of a fixing plate with connection MG1/2" span 150 +/- 10mm incorporating filtration and acoustic coupling (supplied). M G 1/2" downward outlet with integrated non-return valve. Opening/closing button with TOUCH technology with default duty flush (30 sec every 24h without use). Fixed flow rate around 8L/min, temperature adjustable from 18° to 41°C. Unique and patented antiintercommunication hot water (HW) and cold water (CW) system: removal of check valves on the HW and CW mixer inlets. Combination of a compliant French Norm EN1111 thermostatic cartridge and two solenoid valves. 3-year warranty for thermostatic cartridge and electronic components and 10-year warranty for the tap. REF: 75710, MASTERMIX technology, brand SANIFIRST or equivalent approved.



TECHNICAL DATASHEET

Additional Information

Product reference	75710
Previous reference	NC
Brand	Sanifirst
Warranty	10 years against manufacturing defect / 3 years for the thermostatic cartridge and electronic components
Power supply	Battery powered
Special feature 2	Shower
Special feature 3	Thermostatic mixer
Special feature 4	Wall-mounted
Clip-on spout	No
Lever	Chrome-plated zamak knobs
Connection	G'1/2 - EA150+/-10
Flow rate	Fixed approximately 8L/min
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Cartridge	Ceramic cartridge and thermostatic cartridge compliant to French Norm EN 1111
Thermal shock	Yes